



VMF 4200

AUTOMATIC 2 OR 3 HANDS WITH OR WITHOUT DATE



Our VMF 4200 caliber is equipped with a twin barrel and a variable-inertia balance wheel. Versatile, it allows the integration of fixed or modular functions as needed. Customizable and available in a titanium version.



FITTING DIAMETER

25.6 mm (11 1/2")

THICKNESS

3.7 mm

INDICATIONS AND FUNCTIONS

Hours, minutes, central seconds or small seconds at 6 o'clock, date in a window at 3 o'clock or 6 o'clock

BALANCE WHEEL TYPE

Variable inertia with gold regulating screws

FRÉQUENCE

4 Hz (28,800 vph)

INDEX REGULATOR TYPE

Mobile

HAIRSPRING TYPE

Flat

ROTOR TYPE

Customizable (gold, tungsten...)

ROTOR WINDING DIRECTION

Unidirectional, clockwise as seen from the dial side

POWER RESERVE

65 hours

CHRONOMETRY

Fast-rotating twin barrels in series.

NUMBER OF COMPONENTS

198

NUMBER OF JEWELS

30

SPECIFICITIES AND FINISHES

Fully customizable, the finishes follow the codes of haute horlogerie, with particular attention to detail on both the dial side and the bridge side.

- Mainplate with perlage on the dial side and rhodium-plated on the bridge side

- Bridges with perlage and rhodium plating, Côtes de Genève decoration and bicolored engravings

- Diamond-polished bevels, countersinks, and openings

- Polished pivots and shoulders

- Double-sided circled gear wheels

- Secured flat-head screws

FROM 25 PIECES